

Report NO.: NTRE20170461 Page 1 of 10

Test Report No.:	NT	RE201704	l <b>6</b> 1		
Applicant Name:	Gre	e Electric App	liances Inc. of	Zhuhai	
	Wes	t Jinji Rd, Qiar	nshan, Zhuhai, G	Guangdong, China 51907	0
Test item:	Spli	Heat Pump A	ir Conditioner		
Identification:	GUI	0125W/NhA-X		Serial No.:	Engineering
	GUI	D125ZD/A-T			sample
Receipt No.:	RZ0	0340463		Date of receipt:	2017.6.30
Testing location:	Gre	e Electric App	liances Inc. of	Zhuhai	
	Wes	t Jinji Rd, Qiar	nshan, Zhuhai, G	Guangdong, China 51907	0
Test specification	: COM	MMISSION RE	GULATION (EU	) 2016/2281	
	EN	14825:2016			
	EN	EN 14511-2,3:2013			
	EN	12102:2013			
Test Result:	Th	e test items pa	assed the test :	specification(s).	
Testing Laborator	y: Tes	ing Center of 0	Gree Electric App	pliances Inc. of Zhuhai	
tested by:			reviewed	by:	
Date	Name/Position	Signature	Date	Name/Position	Signature

This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

TRF No.: EN 14511 & EN 14825

Report NO.: NTRE20170461 Page 2 of 10



	(EU) 2016/2281 and EN 14511 & EN 14825		
Clause	Requirement - Test	Result - Remark	Verdict

#### **Summary of testing**

- 1. The appliance was tested according to EN 14511.
- 2. The SEER  $_{\sim}$   $\eta$  s,c and SCOP  $_{\sim}$   $\eta$  s,h were calculated according to EN14825.
- 3. All the tests were performed on the outdoor model GUD125W/NhA-X and the indoor model GUD125ZD/A-T.
- 4. The samples are engineering samples without serial numbers.

Test item particulars	
Class of temperature	T1
Type	Split Heat Pump Air Conditioner
Degree of protection	Indoor unit:IPX0 Outdoor unit:IPX4
Supply Connection	Type Y attachment
Possible test case verdicts:	
- test case does not apply to the test object	N/A
- test object does meet the requirement	P(Pass)
- test object does not meet the requirement:	F(Fail)
Testing	
Date of receipt of test item	2017.6.30
Date (s) of performance of tests	2017.7.03-2017.7.20

#### **General remarks**

- This appliance is heat pump type air conditioner, which consist of one outdoor unit and one indoor units.
- >The indoor unit is floor ceiling type air conditioner, which is usually not accessible (only for maintenance purpose).
- ➤ Cooling and heating modes are applied by reverse cycle method. In the heating mode, defrost operation may be applied.
- >The indoor unit is equipped with an infrared wireless battery powered remote control unit.

#### **Critical components:**

Compressor model	Indoor fan motor	Outdoor fan motor
QXFS-F428zX450I	FG250A-ZL	B-SWZ150A(ZWF-150A)

Report NO.: NTRE20170461 Page 3 of 10



(EU) 2016/2281 and EN 14511 & EN 14825			
Clause	Requirement - Test	Result - Remark	Verdict

#### Rating labels and marking:

#### Match table:

Indoor unit	Outdoor unit
GUD125ZD/A-T	GUD125W/NhA-X

The artwork below may be only a draft.



#### FLOOR CEILING TYPE AIR CONDITIONER

Model GUD125ZD/A-T Rated Voltage/Frequency 220-240V ~/50Hz

208-230V~/60Hz

Cooling Capacity 12100W
Heating Capacity 13500W
Rated Input 110W
Air Flow Volume 1800m³/h
Sound Pressure Level 49dB(A)
Weight 40kg

Manufactured Date

GREE ELECTRIC APPLIANCES, INC. OF ZHUHAI





Add: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070

## GREE AIR CONDITIONER OUTDOOR UNIT

Model		GUD125W/NhA-X	
Rated Voltage	380-415V 3N~	Refrigerant	
Rated Frequency	50/60Hz	R32	
Climate Type	T1	Refri. Charge	<u> </u>
Weight	95kg	2.65kg	
Rated Current	8.0A	GWP	675
Moisture Protection	IPX4	CO, Equivalent	1.79t
Operating Pressure ( Discharge Side/Suction Side)			4.6/2.5MPa
Maximum Allowable Pressure			4.6MPa
Manufactured Date			

Contains fluorinated greenhouse gases

GREE ELECTRIC APPLIANCES, INC. OF ZHUHAI





Add: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070

Report NO.: NTRE20170461 Page 4 of 10



(EU) 2016/2281 and EN 14511 & EN 14825			
Clause	Requirement - Test	Result - Remark	Verdict

1	Seasonal space heating energy efficiency of air heating products		
(a)	From 1 January 2018, the seasonal space heating energy efficiency of air heating products shall not fall below the values in Table 1	Measured η <sub>s,h</sub> :157.2% Measured η <sub>s,h</sub> ≥133%	Р
	For multi-split heat pumps, the manufacturer shall establish conformity with this regulation based on measurements and calculations according to Annex III.		N/A
	For each model of outdoor side unit, a list of recommended combinations with compatible indoor side units shall be included in the technical documentation.		N/A
	The declaration of conformity shall then apply to all combinations mentioned in this list.		N/A
	The list of recommended combinations shall be made available prior to the purchase/lease/hire of an outdoor side unit.		N/A
(b)	From 1 January 2021, the seasonal space heating energy efficiency of air heating products shall not fall below the values in Table 2	Measured η <sub>s,h</sub> :157.2% Measured η <sub>s,h</sub> ≥137%	Р
	For multi-split heat pumps the manufacturer shall establish conformity with this regulation based on measurements and calculations according to Annex III.		N/A
	For each model of outdoor side unit, a list of recommended combinations with compatible indoor side units shall be included in the technical documentation.		N/A
	The declaration of conformity shall then apply to all combinations mentioned in this list.		N/A
	The list of recommended combinations shall be made available prior to the purchase/lease/hire of an outdoor side unit.		N/A
2	Seasonal space cooling energy efficiency of cooling	products	
(a)	From 1 January 2018, the seasonal space cooling energy efficiency of cooling products shall not fall below the values in Table 3	Measured η <sub>s,c</sub> :243.7% Measured η <sub>s,c</sub> ≥181%	Р

Report NO.: NTRE20170461 Page 5 of 10



	(EU) 2016/2281 and EN 14511 &	EN 14825	
Clause	Requirement - Test	Result - Remark	Verdict
	For multi-split air conditioners the manufacturer shall establish conformity with this regulation based on measurements and calculations according to Annex III.		N/A
	For each model of outdoor side unit, a list of recommended combinations with compatible indoor side units shall be included in the technical documentation.		N/A
	The declaration of conformity shall then apply to all combinations mentioned in this list.		N/A
	The list of recommended combinations shall be made available prior to the purchase/lease/hire of an outdoor side unit.		N/A
(b)	From 1 January 2021, the seasonal space cooling energy efficiency of cooling products shall not fall below the values in Table 4	Measured η <sub>s,c</sub> :243.7% Measured η <sub>s,c</sub> ≥189%	Р
	For multi-split air conditioners the manufacturer shall establish conformity with this regulation based on measurements and calculations according to Annex III.		N/A
	For each model of outdoor side unit, a list of recommended combinations with compatible indoor side units shall be included in the technical documentation.		N/A
	The declaration of conformity shall then apply to all combinations mentioned in this list.		N/A
	The list of recommended combinations shall be made available prior to the purchase/lease/hire of an outdoor side unit.		N/A
3	Seasonal energy performance ratio of high tempera	ature process chillers	
(a)	From 1 January 2018, the seasonal energy performance ratio of high temperature process chillers shall not fall below the values in Table 5		N/A
(b)	From 1 January 2021, the seasonal energy performance ratio of high temperature process chillers shall not fall below the values in Table 6		N/A
4	Emissions of nitrogen oxides		



	(EU) 2016/2281 and EN 14511 &	EN 14825	ľ
Clause	Requirement - Test	Result - Remark	Verdict
(a)	From 26 September 2018, the emissions of nitrogen oxides, expressed in nitrogen dioxide, of warm air heaters, heat pumps, comfort chillers and air conditioners shall not exceed values in Table 7		N/A
(b)	From 1 January 2021, the emissions of nitrogen oxides, expressed in nitrogen dioxide, of warm air heaters shall not exceed values in Table 8		N/A
5	Product information		
(a)	From 1 January 2018, the instruction manuals for installers and end-users, and free access websites of manufacturers, their authorised representatives and importers shall provide the following product information		Р
(1)	for warm air heaters, the information set out in Table 9 of this Annex, measured and calculated in accordance with Annex III		N/A
(2)	for comfort chillers, the information set out in Table 10 of this Annex, measured and calculated in accordance with Annex III		N/A
(3)	for air-to-air air conditioners, the information set out in Table 11 of this Annex, measured and calculated in accordance with Annex III		Р
(4)	for water/brine-to-air air conditioners, the information set out in Table 12 of this Annex, measured and calculated in accordance with Annex III		N/A
(5)	for fan coil units, the information set out in Table 13 of this Annex, measured and calculated in accordance with Annex III		N/A
(6)	for heat pumps, the information set out in Table 14 of this Annex, measured and calculated in accordance with Annex III		Р
(7)	for high temperature process chillers, the information set out in Table 15 of this Annex, measured and calculated in accordance with Annex III		N/A
(8)	any specific precautions that must be taken when the product is assembled, installed or maintained		N/A



	(EU) 2016/2281 and EN 14511 &	EN 14825	
Clause	Requirement - Test	Result - Remark	Verdict
(9)	for heat generators or cold generators designed for air heating or cooling products, and air heating or cooling product housings to be equipped with such heat or cold generators, their characteristics, the requirements for assembly, to ensure compliance with the ecodesign requirements for air heating or cooling products and, where appropriate, the list of combinations recommended by the manufacturer		Р
(10)	for multi-split heat pumps and multi-split air conditioners, a list of appropriate indoor units		N/A
(11)	for B1, C2 and C4 warm air heaters the following standard text: 'This warm air heater is intended to be connected only to a flue shared between multiple dwellings in existing buildings. Due to a lower efficiency, any other use of this warm air heater shall be avoided and would result in higher energy consumption and higher operating costs'		N/A
(b)	From 1 January 2018, the instruction manuals for installers and end-users, and a part for professionals of the free-access websites of manufacturers, their authorised representatives and importers shall provide the following product information		Р
(1)	information relevant for disassembly, recycling and/or disposal at end-of-life		Р
(c)	The technical documentation for the purposes of conformity assessment pursuant to Article 4 shall contain the following elements		Р
(1)	the elements specified in point (a)		Р
(2)	where the information relating to a specific model has been obtained by calculation on the basis of design, and/or extrapolation from other combinations, the technical documentation shall include details of such calculations and/or extrapolations, and of tests undertaken to verify the accuracy of the calculations undertaken, including details of the mathematical model for calculating performance of such combinations, and of measurements taken to verify this model, and a list of any other models where the information included in the technical documentation was obtained on the same basis		Р

Report NO.: NTRE20170461 Page 8 of 10



	(EU) 2016/2281 and EN 14511 & E	EN 14825	
Clause	Requirement - Test	Result - Remark	Verdict

# Test result of part load according to EN 14825: Calculation of SEER $_{\times}$ $\eta_{s,c}$ in cooling mode:

	ad (Pdesignc)		esignc: 35°C						
Indoc	Indoor Tested Voltage: 230V Frequency: 50Hz								
Outdo	Outdoor Tested Voltage: 400V Frequency: 50Hz								
Test Indoor item DB/WB(°C) Outdoor DB/WB(°C) Tested Pc(W) Tested EER Cd ES									
Α		35/-	12230	3.21	0,25	-			
В	27/19	30/-	8696	5.05	0,25	-			
С	21710	25/-	5645	6.57	0,25	-			
D		20/-	20/- 3829 10.52		0,25	-			
		Psb=	Poff =3.21W; Pck= 0W	; Pto=14.27W					
	Tested SEER 6.168								
	Tested $\eta_{s,c}$ 243.7%								
The calculation method of SEER and η s,c according to the clause 6 of EN14825:2016.									

### Calculation of SCOP, $\eta_{s,h}$ in heating mode:

Gaicai	ation or v		111 1166	iting mode.					
Full load (Pdesignc):10000 W		Tdes	Tdesignc: 35 °C						
Tdesignh: -10°C;		Tbiva	Tbivalent: -7℃; TOL: -10℃ Climate: Average						
Indoor Tested Voltage: 230V		Freq	uency: 50Hz						
Outdoo	r Tested Vol	Itage: 400V	Freq	uency: 50Hz					
Test item	Indoor DB(℃)	Outdoor DB/V	VB(℃)	Tested Ph(W)	Tested COP	Cd	ESP(Pa)		
Α		20/- 7/-8 2/1 7/6 12/11		9041	2.39	0,25	-		
В				5412	3.85	0,25	-		
С	20/-			7/6		3553	5.56	0,25	-
D	_0,			3047	6.85	0,25	-		
Е		TOL		8250	3.35	0,25	-		
F		Tbivaler	t	9041	2.39	0.25	-		
			Psb= P	off=3.21W; Pck= 0W	/; Pto=22.84W				
Tested SCOP					4.005				
Tested η <sub>s,h</sub>				·	157.2%	·			
The calculation method of SCOP and η s,h according to the clause 7 of EN14825:2016.									

Report NO.: NTRE20170461 Page 9 of 10

	(EU) 2016/2281 and EN 2	14511 & EN 14825	
Clause	Requirement - Test	Result - Remark	Verdict

**GREE 构** 

Measured result su	ımmary						
Outdoor side heat excha	nger of air	condition	er: air				
Indoor side heat exchan	ger of air c	onditione	r: air				
Indication if the heater i	s equipped	with a su	pplement	ary heater: no			
Type: compressor driver	n vapour co	ompressio	n				
If applicable: driver of co	mpressor	electric m	notor				
Parameters shall be decl	ared for th	ne average	heating s	eason, parameters for	r the warmer	and cold	er
heating seasons are opti	onal.	1					
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	P <sub>rated,c</sub>	12.1	kW	Seasonal space cooling energy efficiency	η <sub>s,c</sub>	243.7	%
cooling capacity for part temperatures T <sub>j</sub> and inde	•			energy efficiency outdoor tempera	•	load at g	iven
T <sub>j</sub> = + 35 °C	P <sub>c</sub>	12.23	kW	T <sub>j</sub> = + 35 °C	EER	3.21	-
T <sub>j</sub> = + 30 °C	$P_c$	8.69	kW	T <sub>j</sub> = + 30 °C	EER	5.05	-
T <sub>j</sub> = + 25 °C	$P_c$	5.64	kW	T <sub>j</sub> = + 25 °C	EER	6.57	-
T <sub>j</sub> = + 20 °C	$P_c$	3.82	kW	T <sub>j</sub> = + 20 °C	EER	10.52	-
Average heating season indoor temperature 20 ° <i>T j</i>		-		_	ge season coefficient of performance to load at given outdoor temperatures $T_j$ and space genergy $\eta_{s,h}$ 157.2 %		
Rated heating capacity	P <sub>rated,h</sub>	13.50	kW	Seasonal space heating energy efficiency	$\eta_{s,h}$	157.2	%
T <sub>j</sub> = -7 °C	$P_h$	9.04	kW	T <sub>j</sub> = -7 °C	СОР	2.39	-
T <sub>j</sub> = +2 °C	$P_h$	5.41	kW	T <sub>j</sub> = +2 °C	СОР	3.85	-
T <sub>j</sub> = +7 °C	P <sub>h</sub>	3.55	kW	T <sub>j</sub> = +7 °C	СОР	5.56	-
T <sub>j</sub> = +12 °C	P <sub>h</sub>	3.04	kW	T <sub>j</sub> = +12 °C	СОР	6.85	-
Tbiv	$P_h$	9.04	kW	Tbiv	СОР	2.39	-

Page 10 of 10 Report NO.: NTRE20170461



(EU) 2016/2281 and EN 14511 & EN 14825					
Clause	Requirement - Test	Result - Remark	Verdict		

г										
ToL	$P_h$	8.25		kW		ToL	СОР	3.35	-	
T j = - 15 °C (if T OL < - 20 °C)	Pth	-		kW		T j = - 15 °C (if T OL < - 20 °C)	СОР	-	-	
Bivalent temperature	Tbiv	-7	-7			Operation limit temperature	ToL	-10	°C	
Degradation co- efficient for air conditioners	$C_{dc}$	x.x		-						
Power consumption in modes other than 'active mode'										
Off mode	P <sub>OFF</sub>	0.00341		kW		Crankcase heater mode	P <sub>CK</sub>	0	kW	
Standby mode	P <sub>SB</sub>	0.00341	L	kW		Back-up heating capacity	elbu	-	KW	
Thermostat-off mode(cooling/heating)	$P_{TO}$	0.01473 /0.0233 4		kW		Type of energy input		-		
			(	Other it	em	S				
Capacity control		variable	9			air flow rate, outdoor measured(cooling	5900	m <sup>3</sup>	/h	
Sound power level, indoor/outdoor measured(cooling)	L <sub>WA</sub>	L <sub>WA</sub> 61.2/69.2		dB		air flow rate, outdoor measured(heating )	5900	m <sup>3</sup>	/h	
Sound power level, indoor/outdoor measured(heating)	L <sub>WA</sub>	60.9/69	9.5	dB		GWP of the refrigerant	675	kg CO <sub>2 eq</sub> (100 years)		
Contact details for obtaining more Gree Electric Appliances Inc. of Zhuhai										
information on the set	ting of the	'	West 5190		₹d,	Qianshan, Zhuhai	, Guangdon	g, China		

Email: greerzsykt@cn.gree.com

(\*) If Cdc is not determined by measurement then the default degradation coefficient air conditioners shall be 0,25.

Where information relates to multi-split air conditioners, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.