Model	Water Inlet Temperature °C(°F)	Air Inlet Temperature °C(°F)																	
		DB24°C(75.2°F)			DB25°C(77°F)			DB26°C(78.8°F)			DB27°C(80.6°F)			DB28°C(82.4°F)			DB30°C(86°F)		
		WB17°C(62.6°F)			WB18°C(64.4°F)			WB19°C(66.2°F)			WB19.5°C(67.1°F)			WB21°C(69.8°F)			WB22°C(71.6°F)		
		Cooling Capacity (W)	Water Flow (L/s)	Pressure Drop (kPa)	Cooling Capacity (W)	Water Flow (L/s)	Pressure Drop (kPa)	Cooling Capacity (W)	Water Flow (L/s)	Pressure Drop (kPa)	Cooling Capacity (W)	Water Flow (L/s)	Pressure Drop (kPa)	Cooling Capacity (W)	Water Flow (L/s)	Pressure Drop (kPa)	Cooling Capacity (W)	Water Flow (L/s)	Pressure Drop (kPa)
FP-68XD/A-K	5(41)	3300	0,16	30	3330	0,57	31	3860	0,66	40	4220	0,73	46	5010	0,86	63	5850	1,01	82
	6(42.8)	2960	0,14	25	2980	0,51	26	3480	0,6	33	3830	0,66	39	4590	0,79	54	5400	0,93	71
	7(44.6)	2640	0,13	21	2640	0,46	21	3110	0,54	28	3450	0,6	33	4170	0,72	47	4960	0,86	62
	8(46.4)	2320	0,11	17	2320	0,4	17	2760	0,48	23	3080	0,53	27	3770	0,65	38	4530	0,78	52
	9(48.2)	2240	0,11	16	2000	0,35	14	2430	0,42	19	2730	0,47	22	3380	0,58	32	4110	0,71	44
FP-85XD/B-T(E)	5(41)	4250	0,20	18	4400	0,75	19	4950	0,84	22	5310	0,91	24	6120	1,05	29	6860	1,17	35
	6(42.8)	3900	0,19	16	4040	0,69	17	4570	0,78	20	4920	0,84	22	5730	0,98	27	6470	1,11	32
	7(44.6)	3550	0,17	14	3660	0,63	15	4180	0,71	18	4530	0,77	20	5310	0,91	24	6050	1,03	29
	8(46.4)	3190	0,15	13	3290	0,56	13	3800	0,65	16	4140	0,71	18	4910	0,84	22	5660	0,97	26
	9(48.2)	1950	0,09	7	2920	0,5	11	3420	0,58	14	3750	0,64	15	4490	0,77	19	5230	0,89	24
Note: The delta T between water outlet and inlet temperature is 5°C																			